

dimensions in mm
mass: 111 g

25GST2R82 ☉☉ • 1

25GST2R82 ☉☉ • 2

Winding Type

☉☉

-324P

-224P

-216P

-216E

Measured Values

Measuring voltage	V	6	12	24	48
No-load speed	rpm	10300	11300	10300	10800
Stall torque	mNm (oz-in)	81 (11.5)	150 (21)	160 (25)	161 (23)
Average No-load current	mA	300	170	70	40
Typical starting voltage	V	--	--	--	--

Max. Recommended Values

Max. continuous current	A	4.2	2.9	1.45	0.75
Max. continuous torque	mNm (oz-in)	21 (3)	27 (3.8)	30 (4.2)	30 (4.2)
Max. angular acceleration	10 ³ rad/s ²	104	139	152	148

Intrinsic Parameters


Back-EMF constant	V/1000 rpm	0.57	1.05	2.3	4.4
Torque constant	mNm/A (oz-in/A)	5.4 (0.77)	10 (1.42)	22 (3.11)	42 (5.9)
Terminal resistance	ohm	0.4	0.8	3.3	12.5
Motor regulation R/k ²	10 ³ /Nms	14	8	6.8	7.1
Rotor inductance	mH	0.07	0.05	0.1	0.8
Rotor inertia	kgm ² 10 ⁻⁷	10	10	10	10
Mechanical time constant	ms	14	8	6.8	7.1

Executions

		Single Shaft	For E9	HEDS
Gearbox	Page	25GT2R82	25GT2R82	25GT2R82
RG1/8	111	1	2	4
RG1/9	112	1	2	4
K38	110	1	2	4
R32	109	1	2	4
M22	106	5	6	--

- Thermal resistance: rotor-body 6°C/W, body-ambient 13°C/W
- Thermal time constant - rotor / stator: 10 s/450 s
- Max. rated coil temperature: 155°C
- Recom. ambient temperature range: -30°C to +125°C (-22°F to 257°F)
- Max. axial static force for press-fitting without holding shaft (sleeve/ball b.) 500 N/68N
- Axial/radial play (ball bearings) neglectable
- Max axial/radial play (sleeve b.) 150µm/30µm
- Shaft runout: ≤10 µm
- Max. side load at 5 mm from mounting face:
 - sleeve bearings 6N
 - ball bearings 12N
- Motor fitted with ball bearings (sleeve bearings opt.)
- 83 Commutation is recommended for servo applications
- For filter add 'F' to designation before the coil

Max. Recommended Speed



DANAHER MOTION is a registered trademark of Danaher Corporation. Danaher Motion makes every attempt to ensure accuracy and reliability of the specifications in this publication. Specifications are subject to change without notice. Danaher Motion provides this information "AS IS" and disclaims all warranties, express or implied, including, but not limited to, implied warranties of merchantability and fitness for a particular purpose. It is the responsibility of the product user to determine the suitability of this product for a specific application. ©2004 Danaher Motion.