



FEATURES

- Compact and light design.
- Easy paper loading.
- 2 inch paper width.
- Internal 64 bytes flash memory.
- Serial and IRDA ports.
- High speed up to 80 mm/s.
- Print text, graphics and barcode.
- Paper detection.
- Full native and standard Windows drivers.

APPLICATIONS

- Kitchen printer.
- POS (point of sale).
- Data terminal devices.
- Ticketing.

SPECIFICATIONS

Vigor

Printing method	Thermal
Number of dots	384
Resolutions (dots/mm)	8
Printing width (mm)	48
Paper width (mm)	56 ± 0,5
Paper roll diam. max (mm)	85
Max. paper thickness (μ)	80
Paper loading	Easy loading
Printing speed (mm/s)	80
Paper detection	Optosensor
Temperature detection	Thermistor
Head-up or Cover-open detection	Optosensor
Power supply (V/A)	24 ± 10%/1.7
Dot resistance (Ohm)	-
Energy per dot (mJ)	-
Stepper motor (Ohm)	-
Weight (g)	350
Life/reliability	50km/100M pulses
Operating temperature (C°)	0 to 40
Operating humidity (%)	20 to 80 noncond.
Dimensions (WxDxH mm)	-
Expanded Flash memory	16Mbit (512Kbit standard)
Character set	8x13, 14x24, 22x36
Interfaces	RS232C, IRDA (optional)
Graphics	Y
Barcodes	UPCA-E, EAN13-8, Code39, ITF2/5, Codabar, Code128A-B-C
Label/Blackmark detection	Y
Auto Switch-off	Y
Added features	PS/2 Keypad interface for extra input devices

OPTIONS

- IRDA Interface.
- Flash memory expansion.